

TREMBLAY

SOUND MATTERS

TREMBLAY HIGH FIDELITY SERIES SUBWOOFER

SUBWOOFER



AVK-12AC Active Subwoofer Features

- The active subwoofer is specially designed for watching movies and karaoke, which perfectly connects the lower limit of the speaker's low frequency
- The cabinet is made of imported wood to avoid unnecessary resonance and echo, making the sound quality full, pure, more powerful, and lower in distortion
- Luxury car paint process

AVK-12AC active subwoofer parameters

Output power	: 500W
Frequency response	: 30Hz~200Hz (±3dB)
Total harmonic distortion	: <0.1%
Adapt to power supply	: 200V~240V 50/60Hz
Standby power consumption	: <4W
Input sensitivity	: 300mV
Unit configuration	: woofer 1×12"
Dimensions (W×H×D)	: 406mm×443mm×422mm
Weight (net/gross)	: 22kg/22.8kg

TREMBLAY

SOUND MATTERS

TREMBLAY HIGH FIDELITY SERIES SUBWOOFER

SUBWOOFER



AVK-D12000 Active Subwoofer Features

- App Control : Bluetooth
- The active subwoofer is specially designed for watching movies and karaoke, which perfectly connects the lower limit of the speaker's low frequency
- The cabinet is made of imported wood to avoid unnecessary resonance and echo, making the sound quality full, pure, mor powerful, and lower in distroction
- Luxury car paint process

AVK-D12000 active subwoofer parameters

App Control	: Bluetooth
Output power	: 500W
Frequency response	: 30Hz~200Hz (±3dB)
Total harmonic distortion	: <0.1%
Adapt to power supply	: 200V~240V 50/60Hz
Standby power consumption	: <4W
Input sensitivity	: 300mV
Unit configuration	: woofer 1×12"
Dimensions (W×H×D)	: 406mm×443mm×422mm
Weight (net/gross)	: 22kg/22.8kg

TREMBLAY

SOUND MATTERS

TREMBLAY HIGH FIDELITY SERIES SUBWOOFER

SUBWOOFER



AVK-15AC Active Subwoofer Features

- The active subwoofer is specially designed for watching movies and karaoke, which perfectly connects the lower limit of the speaker's low frequency
- The cabinet is made of imported wood to avoid unnecessary resonance and echo, making the sound quality full, pure, mor powerful, and lower in distrotron
- Luxury car paint process

AVK-15AC active subwoofer parameters

Output power	: 1000W
Frequency response	: 30Hz~200Hz (±3dB)
Total harmonic distortion	: <0.1%
Adapt to power supply	: 200V~240V 50/60Hz
Standby power consumption	: <4W
Input sensitivity	: 300mV
Unit configuration	: woofer 1×15"
Dimensions (W×H×D)	: 506mm×543mm×522mm
Weight (net/gross)	: 22kg/22.8kg

TREMBLAY

SOUND MATTERS

TREMBLAY HIGH FIDELITY SERIES LCR

LEFT CENTER



AVK-10F Features

- 44-core all-titanium mesh imported diaphragm tweeter, transparent and clear medium and highs, with distinct layers
- Square metal aluminum horn tweeter, with slender sound and strong penetrating power
- Copper-clad aluminum wire treble voice coil, light (weight), wide frequency response, large sound pressure level
- Independent research and development of double R selvage and imported UKP material paper cone, stable performance, soft and mellow sound
- 65-core copper-clad aluminum wire woofer, rich in low frequency and full in the middle frequency
- Space magnetism, ultra-high magnetic strength, high temperature resistance, no demagnetization
- Adopt self-opening mold aluminum basin frame, not easy to deform, good heat dissipation performance
- Luxury car paint process
- Can be used for Inwall and onwall installations

AVK-10F parameters

Frequency	: 60Hz-20KHz (±3dB)
Sensitivity (1W/1M)	: 95dB
Rated Impedance	: 8Ω
Continuous power	: 350W
Peak power	: 1200W
Configuration	: 2-way
Low frequency unit	: 1×10"
High Frequency Unit	: 1×1.73"

TREMBLAY

SOUND MATTERS

TREMBLAY HIGH FIDELITY SERIES LCR



AVK-28F Features

- Concealed embedded and wall-mounted installation
- Double 8-inch full-frequency unit design, wide sound range large radiation angle, and strong sense of envelopment
- The sound is full of vitality, soft and delicate
- Luxury car paint process
- Can be used for Inwall and onwall installations

AVK-28F parameters

Frequency	: 80Hz-20KHz (±3dB)
Rated Impedance	: 4Ω
Rated power	: 200W
Peak power	: 800W
Sensitivity (1W/1M)	: 94dB
Unit configuration	: woofer 2×8", tweeter 1×1.25"
Installation method	: wall hanging, embedded
AVK-28F Dimensions (W/H/D)	: 260mm×660mm×169.5mm
AVK-28C Dimensions (W/H/D)	: 660mm×260mm×169.5mm
Weight (net/gross)	: 11.1kg/12.1kg

TREMBLAY

SOUND MATTERS

TREMBLAY HIGH FIDELITY SERIES LCR



AVK-08F Features

- Concealed embedded and wall-mounted installation
- Double 8-inch full-frequency unit design, wide sound range large radiation angle, and strong sense of envelopment
- The sound is full of vitality, soft and delicate
- Luxury car paint process
- Can be used for Inwall and onwall installations

AVK-08F parameters

Frequency	: 80Hz-20KHz (± 3 dB)
Rated Impedance	: 4 Ω
Rated power	: 150W
Peak power	: 500W
Sensitivity (1W/1M)	: 94dB
Unit configuration	: woofer 1 \times 8", tweeter 1 \times 1.25"
Installation method	: wall hanging, embedded
AVK-08F Dimensions (W/H/D)	: 260mm \times 430mm \times 159mm
Weight (net/gross)	: 11.1kg/12.1kg

TREMBLAY

SOUND MATTERS

TREMBLAY FIDELITY SERIES LCR



AVK-205F/C Features

- Concealed embedded and wall-mounted installation
- Horn tweeter, double 5-inch full-range unit, wide sound range, large radiation angle
- The cabinet is thin, light in weight and small in size
- The sound is full of vitality, soft and delicate
- Luxury car paint process
- Can be used for Inwall and onwall installations
- Can be used for Inwall and onwall installations

AVK-205F/C parameters

Frequency	: 120Hz-20KHz(±3dB)
Rated Impedance	: 4Ω
Rated power	: 120W
Peak power	: 480W
Sensitivity (1W/1M)	: 95dB
Unit configuration	: full frequency unit 2×5", tweeter unit 1×1"
Installation method	: wall hanging, embedded
Surrounding size (W/H/D)	: 183mm×460mm×120mm
Middle size (W/H/D)	: 460mm×183mm×120mm
Weight (net/gross)	: 3.0kg/3.6kg

TREMBLAY

SOUND MATTERS

TREMBLAY HIGH FIDELITY SERIES SURROUND

SURROUND



AVK-105F Features

- Concealed embedded and wall-mounted installation
- Single 5-inch full-frequency unit, wide sound range and large radiation angle
- The cabinet is thin, light in weight and small in size
- The sound is full of vitality, soft and delicate
- Luxury car paint process
- Can be used for Inwall and onwall installations

AVK-105F parameters

Frequency	: 80Hz-20KHz (±3dB)
Rated Impedance	: 8Ω
Rated power	: 80W
Peak power	: 180W
Sensitivity (1W/1M)	: 94dB
Unit configuration	: full frequency unit 1×5", tweeter unit 1×1"
Installation method	: wall hanging, embedded
AVK-105F Dimensions (W/H/D)	: 185mm×290mm×120mm
Weight (net/gross)	: 1.6kg/2.2kg

RIMLESS CEILING SPEAKERS



AVK-600

- Features:
- Available in 5, 6, and 8 inch
- ABS in ceiling speaker at high performance
- Kevlar driver produces smooth and natural HiFi sound
- Elegant Rimless design
- Good for PA and BGM

AVK-600 parameters

Frequency	: 50Hz-20KHz
Rated Impedance	: 80Ω
Rated power	: 60W
Peak power	: 200W
Sensitivity (1W/1M)	: 90dB
Unit configuration	: 1"x1 (Treble) 6"x1 (Bass)
Installation method	: Ceiling
AVK-600 Dimensions (W/H/D)	: Dia 235mm x 90mm
Weight (net/gross)	: 1.8kg